


LUCIDE



- BULBS -

LED filament bulbs

Ø 3,2cm
H 30 cm

Ø 6cm
H 10,5 cm

Ø 6,4cm
H 14,6 cm

Ø 3cm
H 15 cm

Ø 3,2cm
H 20 cm

Ø 3,2cm
H 25 cm

AMBER COLOR



SMOKE
color



49042/05/62

49042/05/65

49034/05/62

49035/05/62

49035/20/62

49035/25/62

49035/30/62

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ box	qty/ctn	qty/ innerbox
49042/05/62	E27	5W	2200 K	A60 AMBER	260 lm	>80	360 °	30.000		A	1	100	10
49042/05/65	E27	5W	2200 K	A60 SMOKE	200 lm	>80	360 °	30.000		A	1	100	10
49034/05/62	E27	5W	2200 K	ST64 AMBER	260 lm	>80	360 °	30.000		A	1	100	10
49035/05/62	E27	5W	2200 K	T30 AMBER	260 lm	>80	360 °	30.000		A	1	100	10
49035/20/62	E27	5W	2200 K	T32 AMBER	260 lm	>80	360 °	30.000		A	1	100	10
49035/25/62	E27	5W	2200 K	T32 AMBER	260 lm	>80	360 °	30.000		A	1	100	10
49035/30/62	E27	5W	2200 K	T32 AMBER	260 lm	>80	360 °	30.000		A	1	100	10




LED:

High lumen filament,
vintage edison look,
quality chip without shadow,
360° beam angle,
CRI >90 without distortion.



SAFER:

Produces less heat than
former models,
thus reducing the risk of
burns if accidentally
touched.



DRIVER:

Smooth dimming 0% - 100 %
No humming or buzzing.



The look of the former incandescent bulb,
in a contemporary jacket.
These led filament bulbs are easily
recognizable by the extra warm white color
temperature, by the yellow led filament and
the amber or smoke coloured glass.
All are appropriate for use with a dimmer.

LED filament bulbs

Ø 3,2cm
H 20 cm

Ø 3,2cm
H 25 cm

Ø 3,2cm
H 30 cm

GREY COLOR



49047/20/65



49047/25/65



49047/30/65

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ box	qty/ctn	qty/ innerbox
49047/20/65	E27	5W	2200 K	T32 GREY	160 lm	>80	360 °	30.000		B	1	100	10
49047/25/65	E27	5W	2200 K	T32 GREY	160 lm	>80	360 °	30.000		B	1	100	10
49047/30/65	E27	5W	2200 K	T32 GREY	160 lm	>80	360 °	30.000		B	1	100	10



74404-05-65



74404-13-65



LED Globe filament bulbs

Ø 8cm
H 12,2 cm

Ø 9,5cm
H 13,8 cm

Ø 12,5cm
H 17,5 cm

AMBER COLOR

AMBER COLOR



49030/05/65

49032/05/62

49032/05/65

49033/05/62

49033/05/65

SMOKE COLOR

SMOKE COLOR

SMOKE COLOR

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49030/05/65	E27	5W	2200 K	G80 SMOKE	230 lm	>80	360 °	30.000		A	50	10
49032/05/62	E27	5W	2200 K	G95 AMBER	260 lm	>80	360 °	30.000		A	50	10
49033/05/62	E27	5W	2200 K	G125 AMBER	260 lm	>80	360 °	30.000		A	20	10
49032/05/65	E27	5W	2200 K	G95 SMOKE	180 lm	>80	360 °	30.000		A	50	10
49033/05/65	E27	5W	2200 K	G125 SMOKE	180 lm	>80	360 °	30.000		A	20	10

LED filament bulbs

Ø 11,8cm
H 15,8 cm

**BLACK
CLEAR**



49051/04/30

**GREY
COLOR**



49051/04/65

OPAL



49051/04/61

Ø 12,5cm
H 17,5 cm

Ø 8cm
H 12,2 cm



49050/05/61

OPAL



49048/05/61

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49051/04/30	E27	4W	2200 K	BLACK-CLEAR	110 lm	>80	360 °	15.000		B	100	10
49051/04/65	E27	4W	2200 K	GREY	100 lm	>80	360 °	15.000		B	100	10
49051/04/61	E14	4W	2200 K	MATT	310 lm	>80	360 °	15.000		A+	100	10

49050/05/61	E27	5W	2700 K	G125 Matt	450 lm	>80	360 °	15.000		A+	10	10
49048/05/61	E27	5W	2700 K	G80 Matt	450 lm	>80	360 °	15.000		A+	10	10

LED filament bulbs

Ø 3,5cm
H 9,8 cm

Ø 3,5cm
H 11,5 cm

Ø 4,5cm
H 7,7 cm

Ø 4,5cm
H 7,7 cm

AMBER COLOR



49043/03/62



49043/14/62 set 4 pc



49036/03/62




49045/03/62



49046/03/62

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49043/03/62	E14	3W	2200 K	C35 AMBER	115 lm	>80	360 °	15.000		A	100	10
49043/14/62	E14	3W	2200 K	C35 AMBER	115 lm	>80	360 °	15.000		A	10	10
49036/03/62	E14	3W	2200 K	C35 AMBER	115 lm	>80	360 °	15.000		A	100	10
49045/03/62	E27	3W	2200 K	G45 AMBER	120 lm	>80	360 °	15.000		A	100	10
49046/03/62	E14	3W	2200 K	G45 AMBER	120 lm	>80	360 °	15.000		A	100	10



LED filament bulbs “4 steps dimmable”

MATT OPAL

4 steps dimmable by switch



Ø 12,5cm
H 17,5 cm




49067/08/61

Ø 8cm
H 12,2 cm



49066/08/61



Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49066/08/61	E27	8W	2700 K	G80 matt opal	850 lm	>80	360 °	15.000		A+	50	10
49067/08/61	E27	8W	2700 K	G125 matt opal	850 lm	>80	360 °	15.000		A+	20	10

LED filament bulbs “4 steps dimmable”

SMOKE COLOR

4 steps dimmable by switch

Ø 9,5cm
H 13,8 cm



49062/05/65

Ø 12,5cm
H 17,5 cm



49063/05/65

Ø 6,4cm
H 14,6 cm




49064/05/65

Ø 6cm
H 10,5 cm



49065/05/65



Art.numb.	Base	Watt	Kelvin	Smoke	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49062/05/65	E27	5W	2200 K	G95 SMOKE	230 lm	>80	360 °	15.000		A	50	10
49063/05/65	E27	5W	2200 K	G125 SMOKE	230 lm	>80	360 °	15.000		A	20	10
49064/05/65	E27	5W	2200 K	ST64 SMOKE	230 lm	>80	360 °	10.000		A	100	10
49065/05/65	E27	5W	2200 K	ST64 SMOKE	230 lm	>80	360 °	10.000		A	100	10

LED filament bulbs

Ø 9,5cm
H 13,8 cm

CLEAR



49016/05/60

Ø 12,5cm
H 17,5 cm

CLEAR



49017/05/60

Ø 6,4cm
H 14,6 cm

CLEAR



49015/05/60

Art.num.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ ctn	qty/ innerbox
49016/05/60	E27	5W	2700 K	G95 CLEAR	500 - 550 lm	>80	360 °	30.000		A++	100	10
49017/05/60	E27	5W	2700 K	G125 CLEAR	500 - 550 lm	>80	360 °	30.000		A++	20	10
49015/05/60	E27	5W	2700 K	ST64 CLEAR	500 - 550 lm	>80	360 °	30.000		A++	100	10

LED filament bulbs

Ø 3,2 cm
H 21 cm

CLEAR



49031/05/60



Ø 6cm
H 10,5 cm

GOLD



49020/05/10

Ø 4,5cm
H 7,4 cm

GOLD



49021/04/10

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49031/05/60	E27	5W	2700 K	T30 CLEAR	550 lm	>80	360 °	10.000		A++	100	10
49020/05/10	E27	5W	2700 K	A60 GOLD	450 lm	>80	180 °	30.000		A+	100	10
49021/04/10	E27	4W	2700 K	G45 GOLD	320 lm	>80	180 °	30.000		A+	100	10

LED GIANT filament bulbs

Ø 20cm
H 30 cm



49052/08/65

Ø 25cm
H 135 cm



49053/10/65



08426/01/02

SMOKE COLOR

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
49052/08/65	E27	8W	2200 K	G200 SMOKE	330 lm	>80	360 °	10.000		B	1	4
49053/10/65	E27	10W	2200 K	G250 SMOKE	450 lm	>80	360 °	10.000		B	1	4

LED filament **fantasy** bulbs

Ø 14,3cm
H 18,1 cm



80102/06/62

Ø 9,5cm
H 13,5 cm



80104/06/62

Ø 9,5cm
H 16,5 cm



80105/06/62

AMBER COLOR

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
80102/06/62	E27	6W	2200K	amber	550 lm	>80	360 °	10.000	-	A+	1	20
80104/06/62	E27	6W	2200 K	amber	550 lm	>80	360 °	10.000	-	A+	1	20
80105/06/62	E27	6W	2200 K	amber	550 lm	>80	360 °	10.000	-	A+	1	20

LED filament bulbs “day & night sensor”

AMBER COLOR

Ø 6cm
H 10,5 cm



49042/04/62

Ø 6,4cm
H 14,6 cm



49034/04/62

Ø 3cm
H 15 cm



49035/04/62

Ø 9,5cm
H 13,8 cm



49032/04/62

Art.numb.	Base	Watt	Kelvin	clear/ amber	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49042/04/62	E27	4W	2200 K	ST64 AMBER	230 lm	>80	360 °	30.000	no	A+	100	10
49034/04/62	E27	4W	2200 K	ST64 AMBER	230 lm	>80	360 °	30.000	no	A+	100	10
49035/04/62	E27	4W	2200 K	T30 AMBER	230 lm	>80	360 °	30.000	no	A+	100	10
49032/04/62	E27	4W	2200 K	G95 AMBER	230 lm	>80	360 °	30.000	no	A+	50	10

SPECIFICALLY FOR OUTDOOR USE !

Twilight Switch works on twilight principle which automatically switches the lights ON in the evening upon sensing darkness and switches the lights OFF in the morning after sensing daylight.

SENSOR ON <25LUX - OFF >30LUX



display 98074/02/70

10 x 49042/04/62

10 x 49034/04/62

LED Standard filament bulbs

Ø 6cm
H 10,5 cm



49020/05/60

49020/05/67

Ø 4,5cm
H 7,7 cm



49022/04/60

49022/04/67

Ø 4,5cm
H 7,2 cm



49021/04/60

49021/04/67

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49020/05/60	E27	5W	2700 K	A60 CLEAR	500 - 550 lm	>80	360 °	30.000		A++	100	10
49020/05/67	E27	5W	2700 K	A60 MATT	450 - 500 lm	>80	360 °	30.000		A++	100	10
49022/04/60	E14	4W	2700 K	G45 CLEAR	360 lm	>80	360 °	30.000		A+	100	10
49022/04/67	E14	4W	2700 K	G45 MATT	360 lm	>80	360 °	30.000		A+	100	10
49021/04/60	E27	4W	2700 K	G45 CLEAR	360 lm	>80	360 °	30.000		A+	100	10
49021/04/67	E27	4W	2700 K	G45 MATT	280 lm	>80	360 °	30.000		A+	100	10

LED Flame filament & LED SMD bulbs

Ø 3,5cm
H 9,9 cm



49023/04/60



49023/04/67



49023/14/60
SET 4 BULBS

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	qty/ctn	qty/ innerbox
49023/04/60	E14	4W	2700 K	C35 CLEAR	320 lm	>80	360 °	15.000		A+	100	10
49023/04/67	E14	4W	2700 K	C35 MATT	280 lm	>80	360 °	15.000		A+	100	10
49023/14/60	E14	4W	2700 K	C35 CLEAR	280 lm	>80	360 °	15.000		A+	40	10

LED GU10 bulbs



49006/05/30
SET 3/PC 49006/15/30

49006/05/31
SET 3/PC 49006/15/31

49006/05/36
SET 3/PC 49006/15/36


49007/05/60
49008/05/60

Art.numb.	Base	Watt	Kelvin	Color	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
49006/05/30	GU10	5W	3000 K	Black	320 lm	>80	40 °	25.000		A+	1	20
49006/05/31	GU10	5W	3000 K	White	320 lm	>80	40 °	25.000		A+	1	20
49006/05/36	GU10	5W	3000 K	Grey	320 lm	>80	40 °	25.000		A+	1	20
49006/15/30	GU10	5W	3000 K	Black	320 lm	>80	40 °	25.000		A+	3	20
49006/15/31	GU10	5W	3000 K	White	320 lm	>80	40 °	25.000		A+	3	20
49006/15/36	GU10	5W	3000 K	Grey	320 lm	>80	40 °	25.000		A+	3	20
49007/05/60	GU10	5W	2700 K	Glass	350 lm	>80	38 °	30.000		A+	1	100
49008/05/60	GU10	5W	2700 K	Glass	350 lm	>80	38 °	30.000	-	A+	1	100

LED GU10 bulbs “dim to warm”



Ø 5cm
H 5,5 cm



With a dim-to-warm bulb the color temperature is adjustable from 3000 Kelvin (warm white) to 2200 Kelvin (extra warm white).



49009/05/30




49009/05/31




49009/05/36

Art.numb.	Base	Watt	Kelvin	Color	Lumen	Cri	Angle	Hrs.	Dim-mable	Class	bulb/blister	qty/ctn
49009/05/30	GU10	5W	3000 K 2200 K	Black	320 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20
49009/05/31	GU10	5W	3000 K 2200 K	White	320 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20
49009/05/36	GU10	5W	3000 K 2200 K	Grey	320 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20

LED GU10 bulbs “dim to warm” by switch



Dim to warm by switch !



Ø 5cm
H 5,5 cm



49010/05/30



49010/05/31



49010/05/36

Art.numb.	Base	Watt	Kelvin	Color	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
49010/05/30	GU10	5W	2700 K 2500 K 2200 K	Black	350 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20
49010/05/31	GU10	5W	2700 K 2500 K 2200 K	White	350 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20
49010/05/36	GU10	5W	2700 K 2500 K 2200 K	Grey	350 lm	>95	40 °	25.000	DIM TO WARM	A+	1	20

LED G9 & G4 bulbs

Ø 1,5cm
H 4,6 cm



49026/03/31

Ø 1,35cm
H 4,75 cm



Ø 0,96cm
H 3,85 cm



49027/02/31

49029/01/31

Art.numb.	Base	Watt	Kelvin	clear/ matt	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
49026/03/31	G9	3,5W	2700 K	CLEAR	350 lm	>80	360°	15.000		A++	1	100
49027/02/31	G9	2W	2700 K	CLEAR	210 lm	>80	330°	15.000	-	A++	1	100
49029/01/31	G4	1,5W	2700 K	CLEAR	150lm	>80	330°	15.000	-	A++	1	100

LED GU10-ES111 & AR111 bulbs “dim to warm”



Ø 11cm
H 7cm



49041/12/30

Ø 11,1cm
H 5,7cm




49044/10/31

Art.numb.	Base	Watt	Kelvin	Color	Lumen	Cri	Angle	Hrs.	Dim- mable	Class	bulb/ blister	qty/ctn
49041/12/30	ES111- GU10	12W	3000 K 2200 K	Black	820 lm	>95	40 °	30.000	DIM TO WARM	A	1	10
49044/10/31	AR111- G53	10W	3000 K 2200 K	White	500 lm	>95	24 °	30.000	DIM TO WARM	A	1	10



Dim-to-warm: CCT-tunable, dimming not only by reducing the light intensity but also by changing the color temperature, approaching the dimming result of the former incandescent bulb.

22969/12/31



NOTES

LUCIDE BELGIUM
Bisschoppenhoflaan 145
B-2100 Antwerpen
Belgium
Tel: 0032(0)3 366 22 04
info@lucide.be

LUCIDE ASIA Ltd.
Room 1102, 3rd Building
Fantasia MIC Plaza
Nanhai Avenue
Nanshan District
Shenzhen
China
Tel: 0086(0) 755 26681910
info@lucide-asia.com

www.lucide.com